

Industrial Control PC Terminal: CPC.12

12" TFT Colour screen. HI-Performing, professional keyboard.



GENERAL INFO:

The **CPC** is a compact PC touchterminal developed especially for industrial applications within logistics such as luggage-, parcel-, letter- and other forms of sorting systems.

Because of its **supremely high quality keyboard**, the **CPC** is the right choice in places, where you have to key in a lot of data. Due to the PC platform, and the network capabilities (**Ethernet** or **wirelessLAN**), running either under **DOS / WINDOWS / LINUX** it is adaptable to almost any system and software on the market.

Please ask for any option you might need, it may already be available.

STANDARD SPECIFICATIONS:

CPU: Tillamook 266 MMX, **Option:** P433 Celeron or PIII up to 700Mhz

COOLING: Solid state with no airflow(no filter service).

SDRAM: 128 MB up to 256 MB.

FIXED DISK: 2,5" harddisk up to 60 GB. **Option:** Disk On Chip up to 288 MB.

FLOPPY: None. **For service use:** External 3.5" slimline drive in aluchassis with 1,5m cable.

DISPLAY: 12.1" SVGA highbright colour TFT(sun-readable).

TOUCHSCREEN: Infrared: resolution 65x87. **Resistive:** resolution 1024x1024 (using COM1)

INPUT/OUTPUT: COM1+2+3, LPT, keyboard/mouse PS2, 2 x USB, Ethernet, analog CRT, VGA, audio I/O(if supported by motherboard).

POWERSUPPLY: 230VAC (96-264VAC/50-60Hz). **Option:** 24VDC(12-38VDC)

CONSUMPTION: Max. 40W.

HOUSING: Natural anodized aluminum with rubber endbrackets and 12mm commander handles. **HxWxD:** 270x360x90mm.

MOUNTING: Rubber feet for desktop location. Heavy duty swing-arm with turn/tilt function for wall/machine mounting.

Tripod stand for flexible, moveable applications in production areas.

WATER/DUST: Fronthousing IP54. PC connectors are not sealed for water on standard version.

Option: IP54 (waterproof) connector housing with rubber cable reliefs.

TEMPERATURE: -10 to +50 degrees Celsius. Short-term: up to +70 degrees possible.