

Industrial Control PC Terminal: CPC.12

12" TFT Colour screen. HI-Performing, professional keyboard.



GENERAL INFO:

The CPC is a compact PC touchterminal developed especially for industrial applications within logistics such as luggage-, parcel-, letter- and other forms of sorting systems.

Because of its **supremely high quality keyboard**, the CPC is the right choice in places, where you have to key in a lot of data. Due to the PC platform, and the network capabilities (**Ethernet** or **wirelessLAN**), running either under **DOS / WINDOWS / LINUX** it is adaptable to almost any system and software on the market.

Please ask for any option you might need, it may already be available.

STANDARD SPECIFICATIONS:

- CPU:** Tillamook 266 MMX, **Option:** P433 Celeron or PIII up to 700Mhz
- COOLING:** Solid state with no airflow(no filter service).
- SDRAM:** 128 MB up to 256 MB.
- FIXED DISK:** 2,5" harddisk up to 60 GB. **Option:** Disk On Chip up to 288 MB.
- FLOPPY:** None. **For service use:** External 3.5" slimline drive in aluchassis with 1,5m cable.
- DISPLAY:** 12.1" SVGA highbright colour TFT(sun-readable).
- TOUCHSCREEN: Infrared:** resolution 65x87. **Resistive:** resolution 1024x1024 (using COM1)
- INPUT/OUTPUT:** COM1+2+3, LPT, keyboard/mouse PS2, 2 x USB, Ethernet, analog CRT, VGA, audio I/O(if supported by motherboard).
- POWERSUPPLY:** 230VAC (96-264VAC/50-60Hz). **Option:** 24VDC(12-38VDC)
- CONSUMPTION:** Max. 40W.
- HOUSING:** Natural anodized aluminum with rubber endbrackets and 12mm commander handles. **HxWxD:** 270x360x90mm.
- MOUNTING:** Rubber feet for desktop location. Heavy duty swing-arm with turn/tilt function for wall/machine mounting.
Tripod stand for flexible, moveable applications in production areas.
- WATER/DUST:** Fronthousing IP54. PC connectors are not sealed for water on standard version.
Option: IP54 (waterproof) connector housing with rubber cable releifs.
- TEMPERATURE:** -10 to +50 degrees Celsius. Short-term: up to +70 degrees possible.