

SPT.12

Industrial touch PC for food industry



GENERAL INFO:

The SPT is developed especially to withstand wet environments such as in **Meat- and Fishindustries**, where cleaning is essential to the process. In these days, where **veterinarian control** and **food processing** is getting more and more computerized, a rugged and compact unit, with a maximum of flexibility, is needed. Due to the **PC platform** and the **Ethernet**, running either under **DOS** or **Windows**, the SPT.12 is adaptable to almost any system and software on the market.

STANDARD SPECIFICATIONS:

CPU:	PIII-700MHz
COOLING:	Solid state with no airflow(no filter service).
DRAM:	128 MB. Option: 512 MB
FIXED DISK:	20 GB 2,5" Harddisk up to 60 GB.
DISC DRIVES:	Exchangeable diskdrive cassette, located behind fully integrated "snap" cover, includes: 2.5" hard disk(up to 60 GB), CD-RW drive, 3.5" floppy and keyboard / mouse connectors.
DISPLAY:	12.1" SVGA Highbright colour TFT(sun-readable).
TOUCHSCREEN:	Resistiv touch. Hardcoated, smoothly formed frontglass for easy cleaning.
INPUT/OUTPUT:	Keyboard/mouse PS2. Costum output in 25pin D-sub, Ethernet, RS232, USB etc.
POWERSUPPLY:	24VDC(12-38VDC). Max. consumption: 40W.
HOUSING:	HxWxD: 280x390x152
MOUNTING:	PC connectors hidden in 100 mm rubber flexhose mounting device (IP65) with tilt function +30 –20 degrees. Stainless steel mounting stand w. rubber gasket.
WATER/DUST:	IP65. Housing is fully sealed; withstanding damp-cleaning and chemicals.
TEMPERATURE:	-10 to +40 degrees Celsius. Short-term: +70 degrees possible.